



Tabulka připojitelnosti vodičů univerzálních řadových svorek OTL



Objednáací číslo	Typ	Průřez vodiče (mm ²) / Počet vodičů																			Jmenovitý utahovací moment (Nm)	In	Un
			0,75	1	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	300			
T021050 (.B, .YG)	OTL 50/1	Al								1	1	1	1								1,5 Nm (1,5-2,5 mm ²) 5 Nm (4-10 mm ²) 12 Nm (16-50 mm ²)	160 A	1000 V
		Cu			3	3	3	3	3	3	2	1	1										
T021095 (.B, .YG)	OTL 95/1	Al								1	1	1	1	1	1						12 Nm (6-25 mm ²) 22 Nm (35-95 mm ²)	245 A	690 V
		Cu						3	3	3	3	2	1	1	1								
T021120 (.B, .YG)	OTL 120/1	Al									1	1	1	1	1	1					12 Nm (16-35 mm ²) 22 Nm (50-120 mm ²)	280 A	690 V
		Cu									3	3	2	1	1	1							
T021150 (.B, .YG)	OTL 150/1	Al									1	1	1	1	1	1	1				14 Nm (25-50 mm ²) 25 Nm (50-120 mm ²) 30 (70-150 mm ²)	320 A	690 V
		Cu									3	3	2	1	1	1	1						
T021240 (.B, .YG)	OTL 240/1	Al										1	1	1	1	1	1	1	1		26 Nm (35-120 mm ²) 55 Nm (150-240 mm ²)	425 A	690 V
		Cu										3	3	3	2	2	1	1	1				
T021795.R (.SR, .KVR)	OTL 300/1	Al														1	1	1	1	1	30 Nm (95-150 mm ²) 60 Nm (185-300 mm ²)	490 A	690 V
		Cu														3	3	2	1	1			
T022050 (.B, .YG)	OTL 50/1x2	Al								1	1	1	1								1,5 Nm (1,5-2,5 mm ²) 5 Nm (4-10 mm ²) 12 Nm (16-50 mm ²)	2x160 A	1000 V
		Cu			3	3	3	3	3	3	2	1	1										
T022095 (.B, .YG)	OTL 95/1x2	Al								1	1	1	1	1	1						12 Nm (6-25 mm ²) 22 Nm (35-95 mm ²)	2x245 A	690 V
		Cu						3	3	3	3	2	1	1	1								
T021220 (.B, .YG)	OTL 120/1x2	Al									1	1	1	1	1	1					12 Nm (16-35 mm ²) 22 Nm (50-120 mm ²)	2x280 A	690 V
		Cu									3	3	2	1	1	1							
T022150 (.B, .YG)	OTL 150/1x2	Al									1	1	1	1	1	1	1				14 Nm (25-50 mm ²) 25 Nm (50-120 mm ²) 30 (70-150 mm ²)	2x320 A	690 V
		Cu									3	3	2	1	1	1	1						
T022240 (.B, .YG)	OTL 240/1x2	Al										1	1	1	1	1	1	1	1		26 Nm (35-120 mm ²) 55 Nm (150-240 mm ²)	2x425 A	690 V
		Cu										3	3	3	2	2	1	1	1				
T021773.5	OTL 16/5x1	Al								1											1,5 Nm (1,5 mm ²) 2,5 Nm (2,5-6 mm ²) 7 Nm (10-16 mm ²)	5x82 A	690 V
		Cu			3	3	3	2	1	1													
T023050	OTL 50/3x1	Al								1	1	1	1								1,5 Nm (1,5-2,5 mm ²) 5 Nm (4-10 mm ²) 12 Nm (16-50 mm ²)	3x160 A	690 V
		Cu			3	3	3	3	3	3	2	1	1										
T021771 (.1, .1S, .1KV)	OTL 35/P1x2	Al								1	1	1									6 Nm (1,5-16 mm ²) 10 Nm (25-35 mm ²)	270 A	690 V
		Cu			3	3	3	3	3	2	1	1											
T021771	OTL 35/P3x2	Al								1	1	1									6 Nm (1,5-16 mm ²) 10 Nm (25-35 mm ²)	3x270 A	690 V
		Cu			3	3	3	3	3	2	1	1											